

**MATERIAL SAFETY DATA SHEET
FINISHES, COATINGS AND RELATED MATERIALS**

MANUFACTURER: POLOPLAZ **EMERGENCY CONTACT (INFOTRAC #):** 1-800-535-5053
Paradise Park Road
Jacksonville, Arkansas 72076
(501) 985-1172

DATE: February 9, 2009 **Prepared by:** POLOPLAZ Technical Staff
Supercedes Date: February 28, 2007

SECTION I: PRODUCT IDENTIFICATION

PRODUCT NAME: PoloPlaz Supreme Urethane Finish (Semi gloss, Satin, Satin Matte)
PRODUCT CLASS: Oil Modified Polyurethane Wood Floor Finish

SECTION II: HAZARDOUS INGREDIENTS

Ingredient	CAS #	Weight Percent	SARA Title III	Vapor Pressure (mmHg)	Exposure Limits
Stoddard Solvent	6472-88-7	45-50	311/313	2	TLV/ACGIH: 100 NIOSH: none listed
Solvent Naptha Light Aromatic	64742-95-6	5-10	311/313	2	TLV/ACGIH: 100 NIOSH: none listed
Amorphous Silica	7631-86-9	<4%		N/E	OSHA-PEL: 80mg/m3

HMIS® Rating HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0

CALIFORNIA PROPOSITION 65: This product contains no known chemicals known to the State of California to cause cancer or reproductive toxicity.

DOT: Shipping Name - Paint
Hazard Class - 3, Flammable liquid
UN/NA Number - UN1263
Packing Group - PG II
Labels Required - None

SECTION III: HAZARDS IDENTIFICATION

HMIS® Rating HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0

THRESHOLD LIMIT VALUE: N/A

ACUTE HAZARDS

EYE & SKIN CONTACT: Prolonged or repeated exposure may cause defatting of the skin, resulting in drying, cracking, blistering and redness. May cause slight to moderate irritation with possible redness, swelling of mucous membranes, and tearing. Transient injury to the corneal epithelium may also occur.

INHALATION: May cause mucous membrane irritation, nausea, vomiting, disturbed vision, rapid breathing, hyperactivity, fatigue, muscle weakness, headache, light headedness, dizziness, incoordination, tremors, and other central nervous system effects. Extreme exposure may cause respiratory arrest, unconsciousness, kidney and liver impairment.

Ingestion: May cause diarrhea, central nervous system depression, difficulty breathing, incoordination, tremors, weakness, fatigue, and reversible hepatitis. Ingestion may result in aspiration of liquid, producing chemical pneumonitis.

SECTION IV: FIRST AID MEASURES

EYE CONTACT: Immediately flush with plenty of water for 15 minutes & call a physician.

SKIN CONTACT: In case of contact with skin, wash thoroughly with soap and water. Remove & wash contaminated clothing before reuse. (Discard contaminated shoes.)

INHALATION: Remove victim to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Call a physician immediately.

INGESTION: Do not induce vomiting. Get immediate medical attention.

SECTION V: FIRE FIGHTING MEASURES & DATA

LOWER FLAMMABLE LIMIT IN AIR (% BY VOLUME): 0.9 (Lowest component)

FLASH POINT (TEST METHOD): 108°F

EXTINGUISHING MEDIA: Use water fog, carbon dioxide or foam extinguishers.

SPECIAL FIRE FIGHTING PROCEDURES: Water vapor may be ineffective on fire but can protect fire fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear (helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive pressure, self-contained breathing apparatus.

SECTION VI: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Stop spill at source. Dike area & contain. Clean up remainder with absorbent materials. Dispose of collected materials according to Federal, State, & Local Regulations. WASTE DISPOSAL METHOD: Recycle or dispose of observing Federal, State, & Local Regulations. If questions exist, contact the proper agencies.

SECTION VII: HANDLING & STORAGE

HANDLING: Use only with adequate ventilation. Avoid prolonged or repeated breathing of vapor or spray mist. Do not get in eyes, on skin or clothing. Wear OSHA standard goggles or face shield. Consult Safety equipment supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

STORAGE: Keep container tightly closed & upright when not in use to prevent leakage. Ground containers when transferring. Do not flame cut, braze, or weld. Empty container very hazardous! Continue all label precautions. Isolate from oxidizers, heat & open flame.

SECTION VIII: EXPOSURE CONTROLS & PERSONAL PROTECTION

EXPOSURE CONTROLS: If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. Respirator type: organic vapor. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 29 CFR 1910.134.

VENTILATION: Use local, general & mechanical exhaust necessary to keep vapor levels below TLV.

PERSONAL PROTECTION: Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

SECTION IX: PHYSICAL DATA

BOILING RANGE: 281-384°F
PERCENT VOLATILE BY VOLUME: 58.00
SPECIFIC GRAVITY: 0.9
VOLATILE ORGANIC CONTENT (VOC): 4.38 lb/gal - 525g/r
APPEARANCE AND ODOR: Clear, Amber Liquid
SOLUBILITY IN WATER: essentially nil
EVAPORATION RATE (N-BUTYL AC ETATE = 1): 0.11
VAPOR PRESSURE (MM HG @ 68°F): 5
APPEARANCE: Transparent Amber Liquid
ODOR: Solvent Odor

SECTION X: REACTIVITY DATA

STABILITY: stable
MATERIALS & CONDITIONS TO AVOID: isolate from oxidizers such as permanganates, chromates, & peroxides, heat, & open flame. Do not allow product to freeze.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, carbon dioxide from burning.
HAZARDOUS POLYMERIZATION: will not occur

OTHER COMMENTS

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based on data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. Users must have MSDS available in workplace. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.