

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 1 of 13

Revision date: 05.21.2020

Magnum Gym Finish

SECTION 1: Identification

Product identifier

Product name: Magnum Gym Finish

Recommended use of the product and restriction on use

Relevant identified uses: Finishes, Coatings and Related Materials

Uses advised against: For Professional Use Only

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

Poloplaz

1 Paradise Park Road

Jacksonville, AR 72076

501-985-1172

www.poloplaz.com

Emergency telephone number:

United States

Infotrac

1-800-535-5053 (24/7)

SECTION 2: Hazard(s) identification

GHS classification:

Skin irritation, category 2

Flammable liquids, category 3

Skin sensitization, category 1

Carcinogenicity, category 2

Specific target organ toxicity - single exposure, category 3, narcotic effects

Specific target organ toxicity - repeated exposure, category 1

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor

H315 Causes skin irritation

H317 May cause an allergic skin reaction

H336 May cause drowsiness or dizziness

H372 Causes damage to organs (state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 2 of 13

Revision date: 05.21.2020

Magnum Gym Finish

H351 Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

Precautionary statements:

- P264 Wash skin thoroughly after handling
- P280 Wear protective gloves/protective clothing/eye protection/face protection
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion-proof electrical/ ventilating/ lighting/.../ equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing dust/fume/gas/mist/vapors/spray
- P272 Contaminated work clothing must not be allowed out of the workplace
- P271 Use only outdoors or in a well-ventilated area
- P260 Do not breathe dust/fume/gas/mist/vapors/spray
- P270 Do not eat, drink or smoke when using this product
- P201 Obtain special instructions before use
- P202 Do not handle until all safety precautions have been read and understood
- P302+P352 IF ON SKIN: Wash with plenty of water/ ...
- P321 Specific treatment (see ... on this label)
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P362 Take off contaminated clothing and wash it before reuse
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
- P370+P378 In case of fire: Use ... to extinguish
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention
- P363 Wash contaminated clothing before reuse
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P312 Call a POISON CENTER/doctor/.../if you feel unwell
- P314 Get medical advice/attention if you feel unwell
- P308+P313 IF exposed or concerned: Get medical advice/attention
- P403+P235 Store in a well-ventilated place. Keep cool
- P403+P233 Store in a well-ventilated place. Keep container tightly closed
- P405 Store locked up
- P501 Dispose of contents/container to...

Hazards not otherwise classified: None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 8052-41-3	Stoddard Solvent with < 0.1% Benzene content	15-25
CAS number: 64742-47-8	Distillates (petroleum), hydrotreated light	25-35
CAS number: N/A	Alkyd Resin (V)	6-8

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 3 of 13

Revision date: 05.21.2020

Magnum Gym Finish

CAS number: Proprietary	Phenolic Modified Resin (Polymer Exempt)	6-8
----------------------------	--	-----

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If symptoms develop or persist, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eye contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After swallowing:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Skin contact may result in redness, pain, burning and inflammation.

Product is highly flammable. Exposure to sources of ignition may cause physical injury.

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Inhalation may have adverse effects on the central nervous system. Symptoms may include drowsiness, dizziness, headache, nausea and lowering of consciousness. Acute overexposure via inhalation may result in respiratory distress, confusion and unconsciousness.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

Causes damage to organs through prolonged or repeated exposure. Effects are dependent on exposure (dose, concentration, contact time).

Suspected of causing cancer.

Immediate medical attention and special treatment

Specific treatment:

Effects are dependent on exposure (dose, concentration, contact time).

Overexposure via inhalation requires urgent medical treatment.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 4 of 13

Revision date: 05.21.2020

Magnum Gym Finish

Notes for the doctor:

Treat symptomatically.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media:

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Water mist/fog, carbon dioxide, dry chemical or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Flammable liquid. Will be easily ignitable by heat, sparks or flames. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard. Containers may explode when heated. Inhalation or contact with material may irritate or burn skin and eyes. Fire may produce irritating, corrosive and/or toxic gases. Vapors may cause dizziness or suffocation.

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA with a full-face piece operated in positive pressure mode).

Special precautions:

Evacuate non-essential personnel. Ventilate closed spaces before entering. Consider initial evacuation for 300 meters in all directions. If tank/rail car is involved in the fire, ISOLATE for 800 meters in all directions. Fight fire from a maximum distance. Move containers from fire area if you can do it without risk. Use water spray/fog for cooling fire exposed containers. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. Always stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles. If this is impossible, withdraw from area and let fire burn. Stand by, at a safe distance, with extinguisher ready for possible re-ignition. A vapor-suppressing foam may be used to reduce vapors. Avoid unnecessary run-off of extinguishing media which may cause pollution. Do not handle damaged containers unless specialized to do so.

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts.

Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers.

Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. All equipment used when handling the product must be grounded. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling.

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Do not get on skin, eyes or on clothing. Avoid breathing mist.

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 5 of 13

Revision date: 05.21.2020

Magnum Gym Finish

vapor, dust, fume and spray. Do not walk through spilled material. Wash thoroughly after handling. Remove contaminated clothing and launder before reuse.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. A vapor-suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Avoid breathing dust, mist, fumes, vapors or spray. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Take action to prevent static discharges. Handle containers with caution. Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
OSHA	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	PEL: 525 mg/m ³

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 6 of 13

Revision date: 05.21.2020

Magnum Gym Finish

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	PEL: 100 ppm
NIOSH	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	Ceiling Limit: 1800 mg/m ³ (15-min)
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	IDLH: 20000 mg/m ³
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	REL: 350 mg/m ³
ACGIH	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 100 ppm
United States(California)	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 100 ppm
	Stoddard Solvent with < 0.1% Benzene content	8052-41-3	8-Hour TWA: 525 mg/m ³

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

General hygienic measures:

When handling chemical products, do not eat, drink or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes and clothing. Wash contaminated clothing

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 7 of 13

Revision date: 05.21.2020

Magnum Gym Finish

before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance	pale yellow liquid
Odor	mild petroleum odor
Odor threshold	NA
pH	NA
Melting point/freezing point	NA
Initial boiling point/range	161-198C (Stoddard Solvent)
Flash point (closed cup)	101F TCC
Evaporation rate	0.18 (BuAC = 1) (Stoddard Solvent)
Flammability (solid, gas)	NA
Upper flammability/explosive limit	5.6% (Stoddard Solvent)
Lower flammability/explosive limit	0.8% (Stoddard Solvent)
Vapor pressure	27 KPa @ 20C (Stoddard Solvent)
Vapor density	4.9 (Air = 1) (Stoddard Solvent)
Density	0.88
Relative density	NA
Solubilities	not soluble in water
Partition coefficient (n-octanol/water)	NA
Auto/Self-ignition temperature	260C (Stoddard Solvent)
Decomposition temperature	NA
Dynamic viscosity	NA
Kinematic viscosity	NA
Explosive properties	NA
Oxidizing properties	NA

Other information

VOC g/l	482 g/l
---------	---------

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials.

Extreme heat, open flames, hot surfaces, sparks, ignition sources, static electricity and incompatible materials. Vapor accumulation in low or confined areas.

Incompatible materials:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 8 of 13

Revision date: 05.21.2020

Magnum Gym Finish

None known.

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Stoddard Solvent with < 0.1% Benzene content	oral	LD50 Rat: > 5000 mg/kg
	inhalation	LC50 Rat: > 5.5 mg/L (4 h)
	dermal	LD50 Rabbit: >3000 mg/kg
Distillates (petroleum), hydrotreated light	oral	LD50 >5000: Rat mg/kg
	dermal	LD50 >2000: Rabbit mg/kg
	inhalation	LC50 >5.28: Rat mg/L (4h Vapor)

Skin corrosion/irritation

Assessment:

Causes skin irritation.

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes skin irritation.

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data:

No data available.

Substance data: No data available.

Carcinogenicity

Assessment:

Suspected of causing cancer.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC):

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 9 of 13

Revision date: 05.21.2020

Magnum Gym Finish

Name	Classification
Distillates (petroleum), hydrotreated light	Not Applicable

National Toxicology Program (NTP):

Name	Classification
Distillates (petroleum), hydrotreated light	Not Applicable

OSHA Carcinogens: Not applicable

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment:

May cause drowsiness or dizziness.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment:

Causes damage to organs through prolonged or repeated exposure.

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Causes damage to the Central Nervous System through prolonged or repeated exposure via inhalation.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	May be fatal if swallowed and enters airways.
Distillates (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.

Information on likely routes of exposure:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 10 of 13

Revision date: 05.21.2020

Magnum Gym Finish

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	LC50 Oncorhynchus mykiss: 0.14 mg/L (96 hours)
Distillates (petroleum), hydrotreated light	LC50 Pimephales promelas: 41 - 45 mg/L (96 H)
	LC50 Oncorhynchus mykiss: 2.34 - 9.22 mg/L (96 H)
	EC50 Daphnia Magna: 170 - 226 mg/L (24 H)
	EC50 Selenastrum capricornutum (Algae): 19 - 56 mg/L (72 H)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	NOEC Oncorhynchus mykiss: 0.02 mg/L (30 d)

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Readily biodegradable.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	BCF: 39.66 L/Kg ww; Not considered to be bioaccumulative.

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
Stoddard Solvent with < 0.1% Benzene content	Koc at 20°C: 1451

Results of PBT and vPvB assessment

Product data:

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 11 of 13

Revision date: 05.21.2020

Magnum Gym Finish

PBT assessment: This product does not contain any substances that are assessed to be a PBT..

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB..

Substance data:

PBT assessment:

Stoddard Solvent with < 0.1% Benzene content	The substance is not PBT.
Distillates (petroleum), hydrotreated light	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as PBT at concentrations above 0.1%.

vPvB assessment:

Stoddard Solvent with < 0.1% Benzene content	The substance is not vPvB.
Distillates (petroleum), hydrotreated light	This substance is a UVCB and does not contain constituents included in the SVHC candidate list as vPvB at concentrations above 0.1%.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

Contaminated packages:

Not determined or not applicable.

SECTION 14: Transport information

United States Transportation of dangerous goods (49 CFR DOT)

UN number	1263
UN proper shipping name	UN 1263, Paint, Class 3, Packing Group III, Labels 3, Emergency Response 128
UN transport hazard class(es)	None
Packing group	III
Environmental hazards	None
Special precautions for user	None
Additional Information	May be classed as a Combustible Liquid for U.S. Ground

International Maritime Dangerous Goods (IMDG)

UN number	1263
UN proper shipping name	UN 1263, Paint, Class 3, Packing Group III, Labels 3, Emergency Response 128
UN transport hazard class(es)	None
Packing group	III
Environmental hazards	None
Special precautions for user	None
EmS number	1: F-E, 2:S-E

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 12 of 13

Revision date: 05.21.2020

Magnum Gym Finish

UN number	1263
UN proper shipping name	UN 1263, Paint, Class 3, Packing Group III, Labels 3, Emergency Response 128
UN transport hazard class(es)	None
Packing group	III
Environmental hazards	None
Special precautions for user	None
Passenger and cargo	355
Cargo aircraft only	366

SECTION 15: Regulatory information

United States regulations

Inventory listing (TSCA): All ingredients are listed or exempt.

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed.

SARA Section 313 toxic chemicals:

8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Not Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Not Listed
N/A	Alkyd Resin (V)	Not Listed
Proprietary	Phenolic Modified Resin (Polymer Exempt)	Not Listed

CERCLA: None of the ingredients are listed.

RCRA: None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

Massachusetts Right to Know:

8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed

New Jersey Right to Know:

8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed

New York Right to Know:

8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed

Pennsylvania Right to Know:

8052-41-3	Stoddard Solvent with < 0.1% Benzene content	Listed
64742-47-8	Distillates (petroleum), hydrotreated light	Listed

California Proposition 65: None of the ingredients are listed.

SECTION 16: Other information

Safety Data Sheet

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.29.2020

Page 13 of 13

Revision date: 05.21.2020

Magnum Gym Finish

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-2-0

HMIS: 2-2-0

Initial preparation date: 01.29.2020

Revision date: 05.21.2020

End of Safety Data Sheet